

Title: Addressable Light Fixture Module
Serial No.: 10/024,096
Dkt. No.: ZK524/02121

AMENDMENTS TO THE CLAIMS

Claim 1.(Previously Presented) An individually selectable light track fixture, comprising:

a light fixture housing, said housing having a lamp, at least one track runner, a visible light sensor, an infrared receiver, a microprocessor operably connected to memory, said memory having instructions thereon to respond to commands from a remote control unit and a track repeater module and able to:

enter into a programming mode when activated by said visible light sensor;

adjust the brightness of said lamp when said infrared receiver receives associated commands;

store data representing said brightness of said lamp into said memory; and,

recall said stored data when said infrared receiver receives associated commands.

Claim 2. (Previously Presented) The light track fixture of claim 1 in combination with said remote control unit, said remote control unit having a visible laser and an infrared transmitter.

Claim 3. (Original) The light track fixture of claim 2 wherein said remote control unit further comprises a microprocessor operably connected to said memory, said memory having stored thereon a plurality of light fixture commands.

Claim 4. (Original) The light track fixture of claim 1 wherein said light fixture housing further has a visible light programming interface wherein said visible light

Title: Addressable Light Fixture Module

Serial No.: 10/024,096

Dkt No.: ZK524/02121

programming interface is activated when said light track fixture is in said programming mode.

- Claim 5. (Original)The light track fixture of claim 1 further comprising a concentrating lens, said concentrating lens overlaying said visible light sensor.
- Claim 6. (Original)The light track fixture of claim 5 wherein said visible light sensor is comprised of a photo diode.
- Claim 7. (Original)The light track fixture of claim 1 wherein said infrared receiver has a detection angle of about 90°.
- Claim 8. (Original)The light track fixture of claim 6 wherein said photo diode has a half power angle of 40°.
- Claim 9. (Original)The light track fixture of claim 1 further comprising a user defined memory address stored in said memory.
- Claim 10. (Original)The light track fixture of claim 1 wherein said memory further comprises a plurality of memory storage addresses for said data representing said lamp brightness.
- Claim 11. (Original)The light track fixture of claim 1 wherein said at least one track runner is electrically connected to a light fixture track.
- Claim 12. (Original)The light track fixture of claim 1 wherein said light fixture housing is comprised of a light fixture caddy in combination with a light track fixture, said light fixture caddy having a caddy track, said visible light sensor, said infrared receiver, said microprocessor operably connected to said memory, and a caddy track, said light track fixture electrically connected to said caddy track.

Title: Addressable Light Fixture Module
Serial No.: 10/024,096
Dkt. No.: ZK524/02121

Claim 13. (Currently Amended) A track fixture luminaire, comprising:

a housing, said housing having a lamp, a track runner, a laser sensor, an infrared receiver, lamp control electronics, a visible light programming interface, and control circuitry, said control circuitry including programmable storage memory, a programmable address identifier and a microprocessor[.]
wherein said memory is operably connected to said microprocessor and operable to enter into a programming mode when activated by said laser sensor, said memory operable in response to a remote control unit or a track repeater module electrically connected to a track and in associated electrical connection with said track fixture luminaire, to:
adjust the brightness of said lamp using said lamp control electronics;
store data representing said brightness of said lamp in said memory;
recall said stored data when said infrared receiver receives commands.

Claim 14. (Cancelled)

Claim 15. (Original) The track fixture luminaire of claim 13 further comprising a plurality of memory storage addresses for said data representing said lamp brightness.

Claim 16. (Currently Amended) A light track fixture caddy, comprising:

a caddy track for receiving a track light fixture, a track runner, a laser light sensor, an infrared receiver, lamp control electronics, and control circuitry, said control circuitry having a microprocessor operably connected to storage memory wherein said control circuitry is operable to adjust the power supplied to said caddy track[.]

Title: Addressable Light Fixture Module
Serial No.: 10/024,096
Dkt. No.: ZK524/02121

wherein said memory has instructions stored thereon for control of said
microprocessor, said instructions operable to:
store data representing said power supplied to said caddy track in said
memory;
recall said stored data when said infrared receiver receives associates
command; or
recall said stored data when said caddy receives associated commands
through said track runner.

Claim 17. (Cancelled)

Claim 18. (Cancelled)

Claim 19. (Original) A caddy track fixture, comprising: a visible light sensor, an infrared receiver, a caddy track, a microprocessor operably connected to storage memory, control electronics, a track runner wherein said control electronics are operable to adjust power supplied to said caddy track, further wherein said memory has instructions stored thereon to:

enter into a programming mode when activated by said visible light sensor;

adjust the power to said caddy track when associated commands are received by said infrared receiver; store data representing said power supplied to said caddy track into said memory; and,

recall said stored data when said infrared receiver receives associated commands.

Title: Addressable Light Fixture Module
Serial No.: 10/024,096
Dkt No.: ZK524/02121

Claim 20. (Previously Presented) A programmable light fixture, comprising:

a visible light sensor, an infrared receiver, a caddy track, a microprocessor operably connected to storage memory, and control electronics, wherein said control electronics are operable to adjust power supplied to said light fixture, further wherein said memory has instructions stored thereon to:

enter into a programming mode when activated by said visible light sensor;

adjust the power to said light fixture when associated commands are received by said infrared receiver;

store data representing said power supplied to said light fixture into said memory;

store data representing angular positioning for said light fixture into said memory;

and,

recall said stored data when said infrared receiver receives associated commands from said infrared receiver or from signals received on a track runner.